



Product Safety Data Sheet

PRODUCT NAME: Inspired Energy Rechargeable Battery Pack Model: NI1030
TRADE NAME: NI1030 Volts: 10.8
CHEMICAL SYSTEM: Nickel-Metal Hydride Approximate Weight: 520 g

SECTION I – MANUFACTURER INFORMATION

Inspired Energy, Inc.
12705 N. US Hwy 441
Alachua, FL 32615

Telephone: (888) 5-INSPIRE (888-546-7747)

Date Prepared: November 20, 2001

SECTION II – HAZARDOUS INGREDIENTS

Important Note:

The battery should not be opened or burned. Exposure to the ingredients contained within or their combustion products could be harmful

Material Safety Data Sheet Attached:

The cell manufacturer's MSDS is attached.

SECTION III – OPERATING PARAMETERS

Maximum Charge Current: 3000mA with by dT/dt (1.3°C/min) or -dV (555mV)
Minimum Charge Current: 150mA for 36-48h
Maximum Discharge Current: 3A
Recommended Charging Method: Use an SMBus charger of level 2 or higher to provide a maximum 3.0 A constant current charge. The charging cycle will terminate either on dT/dt or -dV.

The information contained within is provided for your information only. This battery is an article pursuant to 29 CFR 1910.1200 and, as such, is not subject to the OSHA Hazard Communication standard requirement for preparation of a material safety data sheet. The information and recommendations set forth herein are made in good faith and are believed to be accurate as of the date of preparation. However, INSPIRED ENERGY, INC. MAKES NO WARRANTY, EITHER EXPRESSED OR IMPLIED, WITH RESPECT TO THIS INFORMATION AND DISCLAIMS ALL LIABILITY FROM RELIANCE ON IT.